



# WL50

Designed to deliver superior-quality water with exceptional performance.

The WL50 meets the demand for large quantities of both hot and cold water, ensuring exceptional water quality. This gravity-fed machine comes equipped with premium filtration and integrated in-tank ultraviolet light. Its enhanced internal design and advanced technology make it ideal for continuously supplying high-quality water in bustling workplaces and public areas throughout the day.

## Advanced technology

The WL50 features three core technologies:



### High performance filtration

This model is available with two filter configurations for high performance filtration, effectively reducing water contaminants and chlorine to improve water taste and odor.



### In-tank LED UV sanitization

Waterlogic's in-tank LED UV technology helps maintain system cleanliness, dispensing great quality water, glass after glass.



### Surface protection technology\*

The key plastic surfaces surrounding the dispensing area are infused with surface protection technology, inhibiting the growth of odor and stain causing microbes, such as bacteria and mold.



\*Surface protection technology protects surfaces from odor- and stain-causing microbes. It does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

## Features

Multiple filtration options: choice of reverse osmosis or carbon filtration to fit local water conditions with mineral add back for great tasting water

Proprietary filtration system allows for easier filter changes with fewer fittings

Gravity-fed storage tank provides additional stored water for the reverse osmosis system or for low pressure installations

The recirculating cold water system passes water by the in-tank LED UV light multiple times every hour to maintain the microbiological purity of the water

Illuminated display and dispense area for precise water temperature selection

The ambient tank system incorporates an air filter designed to minimize the reintroduction of contaminants into the tank while dispensing water

Energy-saving sleep mode significantly reduces power consumption when the unit is not in use

Float-style leak detection system provides extra protection and reduces risks of an accident

Cold tank dispense rate is 3 liters/min, double the rate of a traditional cooler

## Technical specifications

### Types available

Freestanding

### Dimensions

11.8" (W) x 50.3" (H) x 17.2" (D)

### Dispensing area height

11"

### Weight

59 lbs

### Filtration options

Reverse osmosis or carbon filtration

### Storage capacity

Cold tank: ~ 2.2 gal

Hot tank: ~ 1.1 gal

### Compressor

110V/60Hz

### Water temperatures settings

Cold: 37°/ 41°/44° F (default set at 41°F)

Hot: 176°/ 185°/ 199° F (default set at 185°F)

### Dispensing type

Capacitive touch sensor

## Water options

cold

hot

ambient

hot

extra hot



## Number of users 50+

## Contact us today

Waterlogic Commercial Products

[www.waterlogicdealers.com](http://www.waterlogicdealers.com)

(800) 288-1891

[customerservice@waterlogicsusa.com](mailto:customerservice@waterlogicsusa.com)

3175 Bass Pro Drive  
Grapevine, TX 76051

## Tested and certified



The Waterlogic WL50 is certified by IAPMO R&T against NSF/ANSI/CAN 61: Qs1, NSF/ANSI-372, and CSA B483.1 for the specific performance claims as verified and substantiated by test data. The Waterlogic WL50 is also certified to NSF/ANSI-53 for the reduction of lead and cysts and NSF/ANSI-42 for the reduction of Chlorine and Taste & Odor when using the Waterlogic WLLR-12 filter.